

INVENGO XC-AF11 HIGH PERFORMANCE





About Invengo's XC-AF11 High Performance Antenna

Invengo's XC-AF11 antenna offers high gain, ruggedness and excellent shock and vibration resistance in a unique design. The XC-AF11 linear polarized antenna is ideal for transportation, logistics, warehousing and asset tracking applications.



Invengo – the global RFID technology provider – is a leading developer and manufacturer of high quality, intelligent RAIN RFID and HF/NFC connectivity solutions and consumables (tags & inlays) utilized in the Internet of Things. With a focus on RFID innovation, Invengo has created a leading product line in retail, (industrial) laundry, library, (public) transportation, healthcare, and many other industries.

Invengo Technology Pte. Ltd. (SG) is the International Headquarters of Invengo Information Technology Co. Ltd, listed on Shenzhen Stock Exchange (SZSE: 002161.SZ). Employing over 600 people globally, Invengo is one of the largest publicly traded, RFID / IoT oriented companies in the world.


Features

- Operating Frequency
 840 ~ 868 MHz and 902 ~ 928 MHz
- High Gain
- Linear Polarization
- Low VSWR
- Protection Level: IP65
- Durable and clean design
- Simple installation and maintenance





Radiation Pattern


E Phase



Mounting Bracket







America

Invengo Technology Corp. 2700-160 Sumner Blvd. Raleigh, NC 27616 United States of America

Office: +1 919 890 0202 sales.americas@invengo.com

EMEA

Invengo Technologies 180 Voie Ariane – Athélia 1 13600 La Ciotat France

Office: +33 413 96 1111 sales.emea@invengo.com

Product Specifications

Performance Parameter

Operating Frequency 840 ~ 868 MHz

902 ~ 928 MHz

VSWR ≤ 1.4:1 Gain $7.15 ext{ dBi}$ H-Plane HPBW 60° E-Plane HPBW 70° Polarization Linear Antenna Impedance $50 ext{ }Ω$

Environmental

Operating Temperature -40°C to 70°C (-40°F to 158°F) Storage Temperature -40°C to 70°C (-40°F to 158°F)

Humidity Range 5% ~ 95% RH

Protection Level IP65

Physical Parameters

Dimensions 291 x 291 x 52 mm

11.5 x 11.5 x 2 in

Weight Approx. 0,91 kg / 2.0 Lbs

Case Material Plastic ASA, Aluminium

Models

ID XC-AF11-FCC (902~928MHz)

XC-AF11-ETSI (840~868MHz)

V2.4/022018

APAC

Invengo Technology Pte. Ltd

10 Kallang Avenue

Singapore 339510

#05-15 Tower 2, Aperia

Office: +65 6702 3909

sales.apac@invengo.com